

Scan® 500

Automatic colony counter

Ref 436 000



Standards:



Traceability and High technology:



Manufactured under:



Scan® 500 is an automatic color colony counter providing quick and efficient counting of the colonies on the most common supports. Scan® 500 guarantees an excellent reproducibility and the automatic saving of images and results.

TECHNICAL SPECIFICATIONS

- All stainless steel body
 - CMOS color camera
 - M12 lens
 - Zoom x28
 - Resolution: 1 megapixel
 - Counting time: up to 1000 colonies per second
 - Minimum size of colony: 0.1 mm
 - Lighting technology: long-life white LEDs / Dark Field
 - Lighting system: automatic 6 combinations, top and/or bottom light, white or black background
 - Counting: automatic with manual control
 - Counting Petri dishes Ø 55 - 90 mm
 - Counting on pour plating
 - Counting on surface plating
 - Counting on Spiral® plating
 - Counting on circle plating
 - Counting on chromogenic dishes
 - Inhibition zone reader
 - Automatic separation of clustered colonies
 - Export of data to printed report, PDF, jpg, png, bmp, Excel™ recountable session
 - Color detection: 7 colors on the same dish + 1 color to exclude
 - Creation of polygonal exclusion zones
 - Manual control to add or subtract colonies
 - LIMS connection
 - USB connection
 - Compatible with DataLink™ traceability system
 - Data security: modified data traceability in conformity with 21 CFR part 11 / Connexion with LIMS/SIL systems
 - Results/traceability: image / sample number / /comments / date / time
 - Languages: French, English, Japanese, Chinese, Russian, Spanish, German
-
- Voltage and frequency: 100-240V~ 50-60Hz
 - Max power: 20 W
-
- Dimensions (w x d x h): 28.5 x 26.5 x 29 cm, weight: 8.4 kg
 - Box (w x d x h): 50 x 40 x 40 cm, weight: 11 kg

- 3-year warranty
- Software update: 3 year

- In compliance with: 21 CFR part 11, ISO 7218 and AOAC 977.27
- Manufactured under CE, RoHS, WEEE
- Designed and made in France

MINIMUM COMPUTER REQUIREMENTS

- Processor: Intel i3 or superior, 2.8 GHz, quad core recommended
- Operating system: Windows™ 8 or 10
- RAM: 4 GB (2 GB of RAM must be reserved for the exclusive use of the Scan®)
- Equipment: 2.0 USB port free
- Screen: 1280 x 1024 pixels or superior

DELIVERED WITH

- 1 Scan® software
- 1 15 V power supply
- 1 connection cable
- 3 validation plates
- 1 user's manual

OPTIONS / ACCESSORIES

- Ref 410 100 DataLink™: Full traceability system for Petri dishes, from plating to counting with label edition
- Ref 410 120 Sticker for printer: Labels roll for thermal printer - Label size: 45 x 10 mm
- Ref 436 005 Adaptor for Petri dish (55 mm): Adapter for dishes of Ø 55 mm for Scan® 300/500/1200
- Ref 522 000 Bar-code reader: Bar-code reader